



Dimensions "A-LS-LS1-C" are referred to a regular staircase with a slope of 30°. Data are indicative, not binding
The Company reserves the right to undertake all necessary modification without prior notification.

VARIABLES	V65 B.I.							
L Width	1250	1050	1050	1050	830	830	830	830
P Depth	800	900	770	700	770	700	650	600
H1-H1*	1900*	1980	1850	1780	1850	1780	1730	1680
T	1660	1460	1460	1460	1240	1240	1240	1240
T1-T1*	1260*	1065	1065	1065	865	865	865	865
B	1390	1290	1290	1290	1180	1180	1180	1180
N	1920	1720	1720	1720	1500	1500	1500	1500
F 0<M<70	$\alpha < 38^\circ$	380	380	380	380	380	380	380
	$\alpha \geq 38^\circ$	400	400	400	400	400	400	400
F 70<M<150	$\alpha < 38^\circ$	450	450	450	450	450	450	450
	$\alpha \geq 38^\circ$	530	530	530	530	530	530	530
F M>150	$\alpha < 38^\circ$	300+M	300+M	300+M	300+M	300+M	300+M	300+M
	$\alpha \geq 38^\circ$	300+M	300+M	300+M	300+M	300+M	300+M	300+M
D-D**	540/565**	550/575**	515/545**	500/535**	515/545**	500/535**	485/520**	470/505**
E-E**	540/565**	550/575**	475/520**	470/510**	475/520**	470/510**	465/505**	450/490**

Pg 2/4

DATA	CODICE	REV.
04/08/14	8621900	r

VARIABLES	V65 B.I.							
	(1250 800)	(1050 900)	(1050 770)	(1050 700)	(830 770)	(830 700)	(830 650)	(830 600)
A Side ramp	2940	2740	2740	2740	2520	2520	2520	2520
A Front ramp	1950	1740	1740	1740	1520	1520	1520	1520
LS Straight unit side ramp	1150	1250	1120	1050	1120	1050	1000	950
LS Straight unit front ramp	1185	1285	1155	1085	1155	1085	1035	985
LS Curved unit side ramp/with beveled ramp 65 mm.	1360/1320	1400/1350	1300/1250	1230/1190	1250/1200	1180/1130	---/1090	---/1050
LS Curved unit front ramp/with beveled ramp 65 mm.	1360/1340	1400/1370	1300/1270	1230/1210	1250/1220	1180/1150	---/1110	---/1070
C Vertical arms (rest)	2590	2630	2500	2430	2380	2310	2260	2210
C Horizontal arms (working)	1890	1840	1840	1840	1725	1725	1725	1725

Dimensions "A-LS-LS1-C" are referred to a regular staircase with a slope of 30°. Data are indicative, not binding. The Company reserves the right to undertake all necessary modification without prior notification.

VARIABLES		V65 B.R.						
L Width		1050	1050	1050	830	830	830	830
P Depth		900	770	700	770	700	650	600
H1		1820	1690	1620	1690	1620	1570	1520
H2		1250	1120	1120	1120	1120	1120	1120
T		1460	1460	1460	1240	1240	1240	1240
T1		1055	1055	1055	855	855	855	855
B		1290	1290	1290	1180	1180	1180	1180
N		1720	1720	1720	1500	1500	1500	1500
F 0<M<70	$\alpha < 38^\circ$	380	380	380	380	380	380	380
	$\alpha \geq 38^\circ$	400	400	400	400	400	400	400
F 70<M<150	$\alpha < 38^\circ$	450	450	450	450	450	450	450
	$\alpha \geq 38^\circ$	530	530	530	530	530	530	530
F M>150	$\alpha < 38^\circ$	300+M	300+M	300+M	300+M	300+M	300+M	300+M
	$\alpha \geq 38^\circ$	300+M	300+M	300+M	300+M	300+M	300+M	300+M
D—D**		550/575**	515/545**	500/535**	515/545**	500/535**	485/520**	470/505**
E—E**		550/575**	475/520**	470/510**	475/520**	470/510**	465/505**	450/490**

DATA	CODICE	REV.
04/08/14	8621900	r

VARIABLES		V65 B.R.						
		(1050 900)	(1050 770)	(1050 700)	(830 770)	(830 700)	(830 650)	(830 600)
A Side ramp		2740	2740	2740	2520	2520	2520	2520
A Front ramp		1740	1740	1740	1520	1520	1520	1520
LS Straight unit side ramp		1250	1120	1050	1120	1050	1000	950
LS Straight unit front ramp		1285	1155	1085	1155	1085	1035	985
LS Curved unit side ramp/with beveled ramp 65 mm.		1400/1350	1300/1250	1230/1190	1250/1200	1180/1130	---/1090	---/1040
LS Curved unit front ramp/with beveled ramp 65 mm.		1400/1370	1300/1270	1230/1210	1250/1220	1180/1150	---/1110	---/1070
C Vertical arms (rest)		1910	1780	1780	1725	1725	1725	1725
C Horizontal arms (working)		1780	1780	1780	1725	1725	1725	1725

B.I.=INDEPENDENT ARMS

B.R.=RETRACTABLE ARMS

B	Guide rail dimensions, bottom landing
N	Machine dimensions, bottom landing
D	Dimensions with fixed front guard
D**	Dimensions of seat plus fixed front guard
E	Dimensions with front slop
E**	Dimensions of seat plus front slop
A	Minimum landing area
LS	Staircase width

VARIABLES	V65 B.I.-B.R.							
L Width	830	830	830	830	1050	1050	1050	1250
P Depth	600	650	700	770	700	770	900	800
Rated Load up to 45°	300 daN	300 daN	300 daN	300 daN	300 daN	300 daN	250 daN	250 daN
Rated Load over 45°	200 daN	200 daN	200 daN	200 daN	200 daN	200 daN	200 daN	200 daN

Pg 4/4

DATA 04/08/14	CODICE 8621900	REV. r
------------------	-------------------	-----------

TECHNICAL FEATURES

Voltage	Motor Voltage	Auxiliary voltage	Power	Speed
230 [V-mon.]	24 [V-cc]	24 [V-cc]	0.7 [KW]	[8 m/min.]

Dimensions "A-LS-LS1-C" are referred to a regular staircase with a slope of 30°. Data are indicative, not binding
The Company reserves the right to undertake all necessary modification without prior notification.